



Engineering the Future

KRSC-T Range

Powerful clean, dry air in a compact footprint



PRODUCT DESCRIPTION



PRECISION ENGINEERED FOR EFFICIENCY, RELIABILITY AND LONG LASTING PERFORMANCE

Kaishan Air End

- Advanced SKF bearing arrangement
- Minimal inlet pressure drop
- Directly driven

IE4 Main Drive Motor

- Superior premium efficiency
- Better part load efficiency
- Low noise and vibration

Complete Air System

- Includes compressor, air receiver, air dryer and discharge air filter
- Reduced footprint
- All pre-wired, pre-piped and ready to run

Directly Driven Air End

- No belts to adjust or replace
- Lower maintenance costs
- No power loss through belt slippage

Advanced Digital Controller

- Constant monitoring of all vital functions
- Service schedule notification
- Advanced touch control display

Engineered for efficiency and reliability, our 4-22 kW direct-drive compressors deliver consistent 6-10 bar air output with precision and durability for European industries.

Contact Us

 contact@kaishaneurope.com

 www.kaishaneurope.com



Engineering the Future

KRSC-T Range

Powerful clean, dry air in a compact footprint



Fully supported by your local factory authorised and trained distributor.

Contact Details:

TECHNICAL DATA SPECIFICATION

Model	Power kW	Operating pressure (bar)	Volume flow-m3/min		Sound dBA	Weight kg	Dimension mm	Tank L
			8	10				
KRSC-4-T	4	6 - 10	0.56	0.39	72	240	1600*550*1295	200
KRSC-5-T	5.5	6 - 10	0.76	0.62	72	240	1610*550*1295	200
KRSC-7-T	7.5	6 - 10	1.08	0.95	70	245	1700*615*1350	200
KRSC-11-T	11	6 - 10	1.53	1.30	70	270	1700*640*1475	200
KRSC-15-T	15	6 - 10	2.25	1.93	72	280	1700*640*1475	200
KRSC-18-T	18.5	6 - 10	3.02	2.49	72	510	2085*830*1645	400
KRSC-22-T	22	6 - 10	3.45	2.95	73	510	2085*830*1645	400

Performance data according to ISO 1217, Annex E. Technical specifications are subject to change without prior notice. Errors excepted.

Contact Us

 contact@kaishaneurope.com

 www.kaishaneurope.com